



Cooper OFS  
Gaskets for CF  
CF16 - 95+105=200 pcs  
CF40 - 5+15=20 pcs  
CF63 - 8+17=25 pcs

Thermocouple  
20 ÷ 300°C  
50+10=60 pcs

flanges fixed:  
CF16 - 90+20 = 110 pcs (bore)  
CF40 - 3+1 = 4 pcs (bore)  
CF63 - 7+2 = 9 pcs (bore)  
CF63 - 1+1 = 2 pcs (blank)

Reducing flanges:  
CF63/40 - 2 pcs

Connectors "Sagano" Ferrule  
stainless steel socket-welding -  
40+40=80 pcs (41.40.13.010.9)

Inserts: Front O-rings (41.40.35.3700) - 4200 pcs  
Rear O-rings (41.40.35.5704) - 4200 pcs

Heaters:  
stripe 250 ÷ 300°C  
width = 3 cm  
L = 3 m.  
N ≈ 50 pcs  
or 4 cm x 2 m N = 50 pcs

PS - 2 pcs (TMP 56 L/S)  
LD - 1 pcs (Phoenix)  
V2: 3 - CF-R 63 - 2+1+3 pcs  
VAT valve { 57 ser }  
                  { 54 ser }  
V4 - CF40 - 1 pcs  
V6 = 48 - CF-R 16 - 43+7 = 50 pcs  
V49, 50 - CF40/16 - 2+1 ~ 3 pcs  
G1, 2, 4 - absolute gauge  
          1 - to 2000 bar  
          3+1 = 4 pcs  
G3, 5 - full range gauge  
          2+1 - 3 pcs