

<b>COAX CBRH50 50 OHM ( POLYIMMIDE ) IEC 60332-3-24 CERN IS23</b>	<b>Specification</b>		<b>1HRS282</b>
	Rev.	1	Page 1 of 1

### CONSTRUCTION DETAILS

Bare copper conductor 7x0,30 mm  
Several layers of polyimide tapes to diameter 3,5 mm +/- 0,2 mm  
Tinned copper braid overall shield, wire diameter 0,15 mm, coverage 95%, nominal diameter 4,10 mm  
Two layers of polyimide tapes 0,05 mm, overlap 50% colour red  
Nominal overall diameter 4,50 mm +/-0,2 mm

Marking:: CERN - CBRH50 - NOVACAVI - ZERO HALOGEN

### ELECTRICAL AND PHYSICAL CHARACTERISTICS

Electrical resistance inner conductors	< 38,40 ohm/km @ 20°C
Electrical resistance outer conductors	< 9,60 ohm/km @ 20°C
Nominal capacitance	123 pF/m
Nominal impedance	50 OHM
Propagation velocity	57%
Nominal calculated attenuation db/100 m :	
1 MHz          10 MHz          100 MHz	
1.4            5,0            22,0	

Test voltage : 10 kV ac

### OTHER CHARACTERISTICS

Weight	: 43,7 kg/km
Bending radius static min.	: 40 mm
Working temperature	: -269/+260 °C

### REFERENCE STANDARDS

IEC 60332-3-24, IEC 60332-1, IEC 60754-1, IEC 61034-2, CERN IS23

<b>NOVACAVI SPA</b>	Issued	Checked	Date
	T.D.	T.M.	02/04/2009